

TENSAR GEOGRID SOLUTIONS

Soil Stabilisation Guide

TENSAR — THE GEOGRID
MANUFACTURER OF CHOICE




Finding the right solution to repair soft soils is critical to your success. We have a portfolio of products to fit your performance and budget needs for all project conditions...

Conventional Construction

- ➔ Most commonly used construction method.
- ➔ Maximum aggregate thickness and time to construct.


£27.00/m²



Biaxial Geogrid

- ➔ The original Tensar geogrid technology.
- ➔ Reduced thickness when compared to conventional construction.
- ➔ When performance, risk and cost aren't a concern.


£19.50/m²



Tensar H-Series Geogrid

- ➔ Mid-level geogrid performance.
- ➔ Reduced thickness compared with biaxial geogrid.
- ➔ For when lower risk applications require improved project value.


£14.15/m²



Tensar InterAx Geogrid

- ➔ Optimum geogrid performance.
- ➔ Minimum thickness and maximum cost savings.
- ➔ Advanced, precise design methods available.
- ➔ Maximum project value.
- ➔ Improved performance for lower quality fills.

£11.00/m²



Increasing value & performance saving time, cost and carbon >

The Tensar® solutions shown above are illustrative, reflecting typical design parameters and local cost estimates, and should not be adopted within designs without manufacturer guidance. Use Tensar+ for project specific design or contact Tensar® directly for project-specific support. Illustrations above based on design example for access road.



Tensar+

Scan the QR code to sign up for our free, award-winning cloud-based design software platform. www.tensarplus.com



Contact us

Scan the QR code for support. Whether you are looking for project support, have a quick question, or some other need, *please get in touch.*

let us help you with your next challenge: tensar.co.uk email: tensarinfo-uk@cmc.com